



刃先形状

HSS-Co ※生産終了

外径許容差(φD) +0.05
0

R許容差(R) ± 0.02

R寸法	外径	先端径	柄径	柄長	全長
R	φ D	φ D 1	φ d	L 1	L
0.5	12	9	12	45	65
0.6	12	8.8	12	45	65
0.7	12	8.6	12	45	65
0.75	12	8.5	12	45	65
0.8	12	8.4	12	45	65
0.9	12	8.2	12	45	65
1	12	8	12	45	65
1.1	12	7.8	12	45	65
1.2	12	7.6	12	45	65
1.25	12	7.5	12	45	65
1.3	12	7.4	12	45	65
1.4	12	7.2	12	45	65
1.5	13	8	12	45	65
1.6	13	7.8	12	45	65
1.7	13	7.6	12	45	65
1.75	13	7.5	12	45	65
1.8	13	7.4	12	45	65
1.9	13	7.2	12	45	65
2	14	8	12	45	65
2.1	14	7.8	12	45	65
2.2	14	7.6	12	45	65
2.25	14	7.5	12	45	65
2.3	14	7.4	12	45	65
2.4	14	7.2	12	45	65
2.5	16	9	12	50	75
2.6	16	8.8	12	50	75
2.7	16	8.6	12	50	75
2.75	16	8.5	12	50	75
2.8	16	8.4	12	50	75
2.9	16	8.2	12	50	75
3	16	8	12	50	75
3.1	16	7.8	12	50	75
3.2	16	7.6	12	50	75
3.25	16	7.5	12	50	75
3.3	16	7.4	12	50	75
3.4	16	7.2	12	50	75

被削材種	鋳物	炭素鋼	合金鋼	工具鋼	調質鋼	ステンレス鋼	アルミ合金	銅合金	チタン合金	耐熱合金
	FC、FCD	S45C	SCM	SKD	NAK、HPM	SUS	Al	Cu	Ti6Al4V	インコネル
硬度 型番	~200HB	~200HB	~250HB	~35HRC	~45HRC					
CC2	○	○	○	△		○	○	○		

※の寸法は生産を終了しており、在庫が無くなり次第廃盤となります。

CC2**サーキュラコーナーカッター 2枚刃**

Circular Corner Cutter 2-Flutes

R寸法	外径	先端径	柄径	柄長	全長
R	φ D	φ D 1	φ d	L 1	L
3.5	16	7	12	50	75
3.6	16	6.8	12	50	75
3.7	16	6.6	12	50	75
3.75	16	6.5	12	50	75
3.8	16	6.4	12	50	75
3.9	16	6.2	12	50	75
4	20	10	16	50	75
4.25	20	9.5	16	50	75
4.5	20	9	16	50	75
4.75	20	8.5	16	50	75
5	22	10	16	50	80
5.5	22	9	16	50	80
6	24	10	20	50	80
6.5	24	9	20	50	80
7	26	10	20	55	85
7.5	26	9	20	55	85
8	28	10	20	55	85
8.5	28	9	20	55	85
9	32	12	25	60	95
9.5	32	11	25	60	95
10	34	12	25	60	95
※ 10.5	34	11	25	60	95
※ 11	36	12	25	60	95
※ 11.5	36	11	25	60	95
※ 12	38	12	25	65	105
※ 12.5	38	11	25	65	105
※ 13	40	12	32	65	105
※ 14	42	12	32	70	105
※ 15	44	12	32	70	115
※ 16	45	11	32	70	115
※ 17	45	9	32	70	115
※ 17.5	46	9	32	70	115
※ 18	48	10	32	70	115
※ 19	50	10	42	80	130
※ 20	52	10	42	80	130
※ 22	56	10	42	80	130
※ 22.5	57	10	42	80	130